

Claims:

1. A method for performing an Inverse Discrete Wavelet Transform (IDWT) comprising, for a first sub-band level and a second sub-band level in an N level Discrete Wavelet Transform, the steps of:
 - (i) inverse transforming, using filters having associated filter widths, data from associated sub-bands in the first sub-band level, to form processed data in a corresponding sub-band in the second sub-band level; and
 - (ii) inverse transforming, using second filters having the same corresponding associated filter widths, the processed data in conjunction with corresponding data from associated sub-bands in the second sub-band level; wherein steps (i) and (ii) are performed in a pipeline manner.
2. A method according to claim 1, whereby said filters are used in relation to level N, and said second filters are time shared by all other N-1 pairs of consecutive levels N-1 and N-2, ..., 1 and 0, the second filters being substantially applied to only a single pair of levels at a given time
3. A method according to claim 2, whereby time sharing is performed using a time multiplexer which multiplexes data from pairs of levels to the second filters.
4. A method according to claim 2, where data associated with a pair of sub-band levels associated with the second filters, is stored while the second filters are being applied to another pair of sub-band levels.

5. A method according to any one of claims 1 to 4 wherein said filters and said second filters are N dimensional separable IDWT transformers.

6. A method for performing an IDWT in relation to an N level Discrete Wavelet

5 Transform, said method comprising steps of:

(i) applying a first set of $M \times M$ filters to data from associated sub-bands in a first sub-band level, thereby to form $M \times M$ processed data points in a corresponding sub-band in a second sub-band level;

(ii) applying, in a pipeline manner in respect to N-1 succeeding sub-band levels,
10 N-1 corresponding sets of $M \times M$ filters, each corresponding set being applied to $M \times M$ processed data points from a preceding level in conjunction with corresponding data from associated sub-bands in the succeeding sub-band level; thereby to form, in a pipeline manner, a set of $M \times M$ output data points.

15 7. An apparatus adapted for performing an Inverse Discrete Wavelet Transform (IDWT) comprising, for a first sub-band level and a second sub-band level in an N level Discrete Wavelet Transform:

filters having associated filter widths, for inverse transforming data from associated sub-bands in the first sub-band level thereby to form processed data in a
20 corresponding sub-band in the second sub-band level; and

second filters having the same corresponding associated filter widths, for inverse transforming the processed data in conjunction with corresponding data from associated sub-bands in the second sub-band level; wherein the filters and the second filters are arranged in a pipeline manner.

25

8. An apparatus method according to claim 7, wherein said filters are used in relation to level N, and said second filters are time shared by all other N-1 pairs of consecutive levels N-1 and N-2, ..., 1 and 0, the second filters being substantially applied to only a single pair of levels at a given time.

5

9. An apparatus according to claim 8, further comprising:
a time multiplexer which multiplexes data from pairs of levels to the second filters to perform the time sharing.

10

10. An apparatus according to claim 8, further comprising:
storage means for storing data associated with a pair of sub-band levels associated with the second filters while the second filters are being applied to another pair of sub-band levels.

15

11. An apparatus according to any one of claims 7 to 10 wherein said filters and said second filters are N dimensional separable IDWT transformers,

12. An apparatus adapted for performing an IDWT in relation to an N level Discrete Wavelet Transform, said apparatus comprising:

20

a first set of M x M filters for applying to data from associated sub-bands in a first sub-band level, thereby to form M x M processed data points in a corresponding sub-band in a second sub-band level;

N-1 corresponding sets of M x M filters, for applying, in a pipeline manner in respect to N-1 succeeding sub-band levels, each corresponding set being applied to M x
25 M processed data points from a preceding level in conjunction with corresponding data

from associated sub-bands in the succeeding sub-band level; thereby to form, in a pipeline manner, a set of $M \times M$ output data points.

13. A computer readable memory medium for storing a program for apparatus which
5 performs an Inverse Discrete Wavelet Transform (IDWT), said program comprising, for a first sub-band level and a second sub-band level in an N level Discrete Wavelet Transform:

code for a first inverse transforming step for inverse transforming, using filters having associated filter widths, data from associated sub-bands in the first sub-band level,
10 to form processed data in a corresponding sub-band in the second sub-band level; and

code for a second inverse transforming step for inverse transforming, using second filters having the same corresponding associated filter widths, the processed data in conjunction with corresponding data from associated sub-bands in the second sub-band level; wherein the code for the first inverse transforming step and the code for the second
15 inverse transforming step are executed in a pipeline manner.

14. A computer readable memory medium for storing a program for apparatus which performs an IDWT, said program comprising:

(i) first code for an applying step, for applying a first set of $M \times M$ filters to data
20 from associated sub-bands in a first sub-band level, thereby to form $M \times M$ processed data points in a corresponding sub-band in a second sub-band level;

(ii) second code for an applying step, for applying, in a pipeline manner in respect to $N-1$ succeeding sub-band levels, $N-1$ corresponding sets of $M \times M$ filters, each corresponding set being applied to $M \times M$ processed data points from a preceding level in

conjunction with corresponding data from associated sub-bands in the succeeding sub-band level; thereby to form, in a pipeline manner, a set of $M \times M$ output data points.

15 A method for performing an IDWT in relation to an N level Discrete Wavelet Transform, said method comprising, for first sets of data points from associated sub-
5 bands of a first sub-band level, and a second set of data points from a second sub-band level, said first set and said second set of data points each having first data dimensions, steps of:

10 (ii) inverse transforming, using a first computational block having said first data dimensions, said first sets of data points to form a set of processed data points in a corresponding sub-band in the second sub-band level, said set of processed data points having said first data dimensions; and

15 (ii) inverse transforming, using a second computational block having said first data dimensions, the set of processed data points in conjunction with a corresponding set of data points from associated sub-bands in the second sub-band level; wherein steps
20 (i) and (ii) are performed in a pipeline manner thereby to form a set of output data points having said first data dimensions.

16. An apparatus for performing an IDWT in relation to an N level DWT, said
20 apparatus comprising, in respect to a current sub-band level and a subsequent sub-band level;

 a first plurality of parallel convolvers each having a plurality of output data channels, and each said parallel convolver receiving data from a corresponding subband at said current sub-band level;

a second plurality of serial convolvers each receiving data from corresponding ones of said output data channels and producing data for a low-low frequency sub-band of the subsequent sub-band level.

- 5 17. A method for performing an IDWT in relation to an N level DWT, said method comprising, in respect to a current sub-band level and a subsequent sub-band level, steps of:

providing data from corresponding subbands at said current sub-band level to a first plurality of parallel convolvers, each said parallel convolver having a plurality of
10 output data channels;

providing data from corresponding ones of said output data channels to a second plurality of serial convolvers, each said second plurality of serial convolvers producing data for a low-low frequency sub-band of the subsequent sub-band level.